




**SUBMITTAL**

**M-530.31A**

|   |  |
|---|--|
| JOB: _____<br><br>UNIT TAG: _____<br>ENGINEER: _____<br>CONTRACTOR: _____ | REPRESENTATIVE: _____<br><br>ORDER NO. _____<br>SUBMITTED BY: _____<br>APPROVED BY: _____<br><br>DATE: _____<br>DATE: _____<br>DATE: _____ |
|---|--|



# 4-7SC

## Series 530

### Close-Coupled Centrifugal Pumps

**SPECIFICATIONS**

FLOW \_\_\_\_\_ HEAD \_\_\_\_\_  
 HP \_\_\_\_\_ RPM \_\_\_\_\_  
 VOLTS \_\_\_\_\_  
 CYCLE \_\_\_\_\_ PHASE \_\_\_\_\_  
 ENCLOSURE \_\_\_\_\_  
 APPROX. WEIGHT \_\_\_\_\_  
 SPECIALS \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**MATERIALS OF CONSTRUCTION**

BRONZE FITTED     ALL IRON

**MAXIMUM WORKING PRESSURE**

175 psi (12 bar) W.P.  
 with 125# ANSI flange drilling

**TYPE OF SEAL**

- 530 Standard Seal (Buna-Carbon/Ceramic)
- 530 -F Standard Seal w/ Flush Line (Buna-Carbon/Ceramic)
- 530 -S Stuffing Box construction w/ Flushed Mechanical Single Seal (EPR-Tungsten Carbide/Carbon)
- 530 -D Stuffing Box construction w/ Flushed Double Mechanical Seal (EPR-Carbon/Ceramic) Requires external water source
- 530 -PF Stuffing Box Construction w/ Flushed Packing (Graphite Impregnated Teflon)

