




SUBMITTAL

M-530.36A

JOB: _____ UNIT TAG: _____ ENGINEER: _____ CONTRACTOR: _____	REPRESENTATIVE: _____ ORDER NO. _____ SUBMITTED BY: _____ APPROVED BY: _____ DATE: _____ DATE: _____ DATE: _____
---	--



2-1/2-9SC

Series 530

Close-Coupled Centrifugal Pumps

SPECIFICATIONS

FLOW _____ HEAD _____
 HP _____ RPM _____
 VOLTS _____
 CYCLE _____ PHASE _____
 ENCLOSURE _____
 APPROX. WEIGHT _____
 SPECIALS _____

MATERIALS OF CONSTRUCTION

- BRONZE FITTED ALL IRON
 ALL BRONZE †
 †All bronze not available in stuffing box configuration

MAXIMUM WORKING PRESSURE

- 175 psi (12 bar) W.P.
 w/ 125# ANSI flange drilling

TYPE OF SEAL

- 530 Standard Seal (Buna-Carbon/Ceramic)
 530 -F Standard Seal w/ Flush Line (Buna-Carbon/Ceramic)
 530 -S Stuffing Box construction w/ Flushed Mechanical Single Seal (EPR-Tungsten Carbide/Carbon)
 530 -D Stuffing Box construction w/ Flushed Double Mechanical Seal (EPR-Carbon/Ceramic) Requires external water source
 530 -PF Stuffing Box Construction w/ Flushed Packing (Graphite Impregnated Teflon)

