


<b>JOB:</b>  <b>UNIT TAG:</b> <b>ENGINEER:</b> <b>CONTRACTOR:</b>	<b>REPRESENTATIVE:</b>  <b>ORDER NO.</b> <b>SUBMITTED BY:</b> <b>APPROVED BY:</b>	<b>DATE:</b> <b>DATE:</b> <b>DATE:</b>
---	---	--



# 8-13SC

## Series 530

### Centrifugal Pumps - Closed-Coupled

**SPECIFICATIONS**

FLOW \_\_\_\_\_ HEAD \_\_\_\_\_

HP \_\_\_\_\_ RPM \_\_\_\_\_

VOLTS \_\_\_\_\_

CYCLE \_\_\_\_\_ PHASE \_\_\_\_\_

ENCLOSURE \_\_\_\_\_

APPROX. WEIGHT \_\_\_\_\_

SPECIALS \_\_\_\_\_

**MATERIALS OF CONSTRUCTION**

BRONZE FITTED

**MAXIMUM WORKING PRESSURE**

175 psi (12 bar) W.P.  
with 125# ANSI flange drilling  
(Max. Suction Pressure 75 psi [5.2 bar])

**TYPE OF SEAL**

- 530 -S, Stuffing Box Construction w/ Flushed Single Mechanical Seal EPR-Carbon NiResist Max 250°F[120°C]
- 530 -S, Stuffing Box Construction w/ Flushed Single Mechanical Seal EPR-Carbon/Tungsten Carbide Max 250°F[120°C]
- 530 -S, Stuffing Box Construction w/ Flushed Mechanical Seal Buna-Carbon/Ceramic Max 225°F[106°C]

